Nº					N	OTE	S (ENCI	RCLED NU	MBERS)					
①	POWER CIRCUITS WIRED FOR 115 V. A.C. OR D.C. OPERATION.													
2	WIRE COLOR CODE: BK BLACK G GREEN R RED Y YELLOW W-BR WHITE-BROWN W-P WHITE-PURPLE BR BROWN O ORANGE S SLATE W-BK WHITE-BLACK W-G WHITE-GREEN W-R WHITE-RED BL BLUE P PURPLE W WHITE W-BL WHÎTE-BLUE W-O WHITE-ORANGE W-S WHITE-SLATE W-Y WHITE-YELLOW													
3		<u>=</u> D	EN	OTE	S	SHIEL	DED WIF	RES.						
(4)	CONNECTORS	VI	EWI	ED	FR	OM SO	LDER TE	RMINAL E	NDS					
3	SHIELDING TO PROTRUDE THROUGH CONTACT BOX UP TO 1/32 MAX. AFTER ELECTRICAL NOISE SUPPRESSOR IS INSTALLED, SOLDER SHIELDED WIRE TO 151365 GROUNDING LUG.													
6	DEN SECURE TO							VITH ACCE	SSORY.					
0	STRAP NECE	SSA	RY	F)R	OPERA	TION W	ITH LES	U 7					
•	WHEN THE PA MOTOR LEAD BLOCK INSTE	CON	INE	CTS	T	O TERM	INAL 3	ART SWITC	H IS SUPP R TERMIN	PLIED, AL			-	
9	ACCESSORY GROUP NUMBER	KE		OAF K	₹0,	TIME DELAY MECH.	SIG.LINE BREAK MECH.	FEED OUT	LOCAL REVERSE LINE FEED	BACK	LINE			
	118	X	X			X	X		X	Х				
	131	X	X			_	X	_						
	125,127	X	X				X							
	158	×	X			_								
	179	X	-		-			X						
	212	X					X		×	×			<u> </u>	
	126	X	X		-	X	X							
	231	 <u> </u>	×		_						X			
		\vdash												
ļ									-					
0	FILTER NET	WOF	 ₹K											
	STRAP NEC				FO	R OP	FRATIO	N WITH	ACCESS	SORY	GRO	JP 23		
0														
(2)	TAPE AND TIE BACK MARGIN INDICATOR SWITCH WIRES. (YELLOW & RED.) BOTH ENDS FOR ACC. GROUP 231													
					÷									
- 1														



